

DEUTSCHLATEX



DESCRIPTION

Superior quality acrylic paint, with high resistance to different weather conditions, based on acrylic emulsion

PROPERTIES OF PRODUCT

- Matte surface
- Superior whiteness
- Available in 4 bases W, P, D et TR
- Very good workability and leveling properties
- Very good hiding power
- Good adhesion properties and short drying time

RECOMMANDATIONS OF USE

It is used in all interior walls, new, old and already painted with cement-based plaster, cement, lime, etc., in any type of exterior space, striped plaster, plaster finishing, grout facade, etc. and also for painting concrete surfaces treated with primer.

TECHNICAL DATA

Resin	Acrylic copolymer
Density EN ISO 2811-1	1,45±0,02 gr/ml
Résidu sec EN ISO 3251	65%
Dilution	10 – 15%
Viscosity	110 ± 5 KU
Cons.	9.5+-1m2
Drying time between 2 layers	2 - 4 hours
VOC in ready product (European Directive 2004/42/EC) (g/l)	≤ 10
VOC ambiantes emissions simulation ISO 16000 (mg/m ³)	≤ 0.2
Coverage EN ISO 6504-3	≥ 99.5% Class I
Washing resistance ISO 11998	Class I

APPLICATION GUIDELINES

- Method of application: Brush, roller or spray
- Dilution: It is recommended to dilute 10-15% with water, except for bases D and TR which are not recommended to be diluted more than 5%.

PREPARATION OF SURFACE

Surfaces must be completely dry, clean and free of dust and elements that interfere with paint adhesion. Repair all cracks and damaged parts using products from the range of Deutschcolor, Spachtel Massen, etc. Then, it is recommended to apply the Macht Haftgrund liner, diluted with water 1:3. When applying the primer, avoid creating a film, which then creates problems with the paint sticking to the support.

PREPARATION OF PRODUCT

Dilute DeutschLatex product with 10-15% water, except for D and TR bases, which are recommended to be diluted no more than 5% water, ensuring that it is well mixed with the painting. Use an electric mixer on low speed to achieve as even and thorough a mixture as possible.

APPLICATION OF PRODUCT

Application of the product DeutschLatex can be applied by brush or roller. The application cycle includes at least the application of two coats of paint. The time required between the two coatings is 2-4 hours depending on weather conditions, temperature and humidity. Clean work tools with water before the paint dries.

PACKAGING

5KG, 25KG, 40KG.

STORAGE

24 months if stored in a dry place, away from heat sources, at a temperature between +5°C and +30°C, protect it from freezing.

HEALTH AND SAFETY INFORMATION

Keep out of the reach of children. In case of eye contact or swallowing, seek medical attention immediately and show contents of container. Do not flush product down drains.

NOTES

- In new concrete surfaces, it is recommended to use the product at least after approx. 30-40 days.
- It is recommended to avoid applying the product at temperatures below 5 °C or shortly before rain.

