

## FM PRIMER



### DESCRIPTION

Acrylic, resin-based primer

### RECOMMENDATIONS FOR USE

FM PRIMER can be applied as a primer layer in various supports, such as: old tiles, smooth surfaces, natural stones, floor surfaces of cement, wood and metal. It is used to give the support the desired qualities before the application of cement-based tiles adhesive.

### INSTRUCTIONS FOR PREPARATION

The surface where FM PRIMER will be applied must be free of moisture, dust and oils.

### RECOMMENDATIONS FOR USE

FM PRIMER can be applied as a primer layer in various supports, such as: old tiles, smooth surfaces, natural stones, floor surfaces of cement, wood and metal. It is used to give the support the desired qualities before the application of cement-based tiles adhesive.

### TECHNICAL DATA

Form:	Liquid
Color:	Yellow
Density:	1,05 Kg/l
pH:	7
Solid content:	30%
Viscosity:	30 MPa.s

### APPLICATION OF PRODUCT

FM PRIMER is ready for use, and is applied directly to the support with a roller or brush. Tile adhesive can be applied after an hour, as long as FM PRIMER is sticky.

### STORAGE

18 months if stored in its original packaging and protected by frost and direct exposure to sun.

### CONSUMPTION

0.2- 0.3 Kg/m<sup>2</sup>

### PACKAGING

1Kg / 5Kg / 10Kg plastic bottles

### HEALTH AND SAFETY INFORMATION

Keep out of reach of children. In case of contact with the eyes or swallowing, please seek medical advise immediately and show the contents of the container. Do not dispose the product into drains.

