

HYDRO PRIMER



DESCRIPTION

Elastomeric primer, for surfaces where waterproofing will be applied.

CHARACTERISTICS

Elastomeric primer for surfaces where waterproofing will be applied. Aqueous polymer dispersion is applied on porous surfaces thus significantly increasing adhesiveness between elastomeric-based hydro isolators and support. HYDRO PRIMER has penetrating properties in all pores of the surface where waterproof will be applied, thus improving and enhancing the adhesive ability between the waterproof and the surface that will be waterproofed.

RECOMMENDATIONS FOR USE

HYDRO PRIMER is a ready to use PRIMER, which reinforces considerably waterproof adhesion on surfaces made of concrete, mortar, plaster and gypsum panels.

TECHNICAL DATA

Form:	Liquid
Colour:	Yellow
Density:	1,05 Kg/l
pH:	7
Solid content:	20%
Production	30 MPa.s
viscosity: Storage	50 MPa.s
viscosity:	2%

APPLICATION OF PRODUCT

The surfaces to be treated with PRIMER should be completely dry and clean, free of presence of dust. It is recommended to stir it before application. It is easily applicable with a brush or roller on surfaces, before the application of elastomeric waterproof.

STORAGE

The product can be stored for 18 months in its original packaging and in a dry place. You should avoid exposing the product to low temperatures (freezing) and high temperatures.

CONSUMPTION

200 - 300 g/m², depending on the porosity of the surface to be treated.

PACKAGING

1Kg / 5Kg / 10 Kg plastic bottles

HEALTH AND SAFETY INFORMATION

Keep out of reach of children. In case of contact with the eyes or swallowing, please seek medical advise immediately and show the contents of the container. Do not dispose the product into drains.

ATTENTION!

The product is recommended to be applied in the limits of temperatures from +5°C to +35°C

