

SPATORELLA BLEU



DESCRIPTION

Cement based grout made up of filler with selected granulometry and special additives for indoor use

PRODUCT PROPERTIES

- Does not create cracks
- Strong bonding
- White colour
- Final smooth finish
- Easy application and grinding
- Does not shrink even with thick film

RECOMMENDATIONS FOR USE

It is used for wall polishing on all the interior dwelling spaces where we want to create a smooth and fair surface for painting inner wall surfaces, used for rendering the interior of the ceiling, concrete surfaces in the interior, room, kitchen, toilette surfaces, etc.

TECHNICAL DATA

| | |
|---------------------------------------|---------------------------|
| Basis | Acrylic copolymer |
| Density EN ISO 2811-1 | |
| Dry residue EN ISO 3251 | 80% |
| Mixing ratio | Ready for use |
| Colour | White |
| Tensile adhesion strength in concrete | ≥ 0,8 N/mm ² |
| Consumption: | |
| Structure 1.5mm complete | 2.5-3.0 Kg/m ² |
| Structure 2mm complete | 3.0-3.5 Kg/m ² |
| Structure 2mm complete | 3.5-4.0 Kg/m ² |
| Structure 3mm complete | 4.5-5.0 Kg/m ² |
| Drying time | 24 hours |
| Resistance to humidity | W1 |

APPLICATION GUIDELINES

- Application method: SPATORELLA BLEU can be applied through a spatula.
- Thinning: 5 liters of water / 15 kg

SURFACE PREPARATION

The surfaces should be completely dry, clean and free from dust and elements that hinder the adhesion of the product.

PRODUCT PREPARATION

Fill a container with the required amount of water and then add a SPATORELLA BLEU product in a mixture with an electric mixer. Mix the product until a homogeneous mass without grains that make application difficult is obtained.

APPLICATION OF PRODUCT

Application of product SPATORELLA BLEU is done with a metal notched trowel. Spread the product on the surface to be rendered and bring it to the required thickness. The application thickness of a coating shall not exceed 3 mm. The product must be applied in two coatings. Clean the spatula and other working tools with water immediately after application.

PACKAGING

15 kg

STORAGE

12 months if stored in a dry place, away from heat sources, at a temperature between +5°C and +30°C. Protect it from frost.

HEALTH AND SAFETY INFORMATION

Keep out of reach of children. In case of contact with the eyes or swallowing, please seek medical advise immediately and show the contents of the container. Do not dispose the product into drains.

NOTES

- In fresh concrete surfaces the product should be applied at least after 30-40 days.
- It is recommended to avoid application of product at temperatures below 5°C.

