

FLUIDCRET 05



DESCRIPTION

Plasticizer, Type A - additive for waterproofing in concrete preparation.

CHARACTERISTICS

Plasticizer, Type A - additive for waterproofing in concrete preparation. Fluidcret 05 is a liquid additive that acts as a plasticizer and waterproofing agent in concrete and, thus offering the following advantages:

- Significantly increases water impermeability in positive and negative pressure or capillary absorption.
- Improves workability without the need to increase the amount of water.
- Eliminates the air within the concrete mass.
- Does not contain chlorides and other irritating agents.
- It is compatible with all types of Portland cement.

RECOMMENDATIONS FOR USE

Fluidcret 05 is a necessary additive for the preparation of concretes with high resistance to compression, for concretes exposed to atmospheric agents, as well as for concrete that will immerse into the water.

PRODUCT PREPARATION

Fluidcret 05 can be added:

- In the mixer during the preparation of concrete.
- In pre - prepared concrete before use. In this case, concrete mixer must mix the concrete for an additional 3-5 minutes, in order to achieve a uniform distribution across the concrete mass.

TECHNICAL DATA

Form:	Liquid
Colour:	Brown
Density:	1,05 Kg/l
pH:	9
Solid content:	30%
Dosage:	0,5% - 1% on ciment
Viscosity:	50 MPa.s
Alkaliniteti:	2%

DOSAGE

0.3 - 0.5 Kg per 100 Kg cement

CONSUMPTION

0.2- 1 Kg/m²

PACKAGING

5 Kg / 20 Kg / 100 Kg plastic bottles

STORAGE

18 months after production date, if the product is stored in original and unopened packaging, at temperatures between +5°C and +35°C and protected from direct exposure to sun and frost.

HEALTH AND SAFETY INFORMATION

Keep out of reach of children. In case of contact with the eyes or swallowing, please seek medical advise immediately and show the contents of the container. Do not dispose the product into drains.

