

PICASSO J'ADORE VINYL



DESCRIPTION

Excellent quality emulsion paint for interior and general exterior use

PRODUCT PROPERTIES

- Great covering power
- Great whiteness
- Smooth matte finish
- Very good working and leveling properties
- Strong adhesion and quick drying
- Without ammonia
- Cost-effective solution for frequent painting and refreshing

RECOMMANDATIONS OF USE

Interior and exterior surfaces of plaster, concrete, brick, wood, stucco, plasterboard, plastic, etc.

TECHNICAL DATA

Resin	Acrylic Copolymer
Density (white):	1,60±0,02 gr/ml
Production viscosity (white):	110±5 KU 23°C
Storage viscosity (white):	110±7 KU 23°C
Spreading rate	until 9m ² /lit for each layer
Full dry (White):	20±10 min
Coverage time(White):	50±10 min
Full dry (shades):	30±10 min
Coverage time (shades):	2±½ hours (Drying and coverage time may be extended under low temperature and high relative humidity conditions)
Shades:	Available in white and in thousands of shades via the deutschcolor (dcs) coloring system. It can also be tinted with dc basics emulsion dyes.
VOC (Volatile Organic Compounds)	Limit value for this product category α/a "matt interior walls and ceilings (gloss<25@60o)": 30g/l (2010). The product contains max. 29g/l.

APPLICATION GUIDELINES

- Method of application: Brush, roller or spray
- Dilution: It is recommended to dilute 10-15% with water, except for bases D and TR which are not recommended to be diluted more than 5%.

PREPARATION DE SURFACE

Surfaces must be completely dry, clean and free of dust and elements that interfere with paint adhesion. Repair all cracks and damaged parts using products from the range of Deutschcolor, Spachtel Massen, etc. Then, it is recommended to apply the Macht Haftgrund liner, diluted with water 1:3. When applying the primer, avoid creating a film, which then creates problems with the paint sticking to the support.

PREPARATION OF PRODUCT

Dilute the Picasso J'adore Vinyl product with 10-15% water, except for the D and TR bases, which it is recommended not to dilute with more than 5% water, making sure that it is well mixed with the paint. Use an electric mixer on low speed to achieve as even and thorough a mixture as possible.

APPLICATION OF PRODUCT

Applying Picasso J'adore Vinyl is applied with a brush or roller. The application cycle includes at least the application of two coats of paint. The time required between the two coatings is 2 to 4 hours depending on weather conditions, temperature and humidity. Clean work tools with water before the paint dries.

PACKAGING

5KG, 10KG, 25KG, 40KG

STORAGE

24 months if stored in a dry place, away from heat sources, at a temperature between +5°C and +30°C, protect it from freezing.

HEALTH AND SAFETY INFORMATION

Keep out of the reach of children. In case of eye contact or swallowing, seek medical attention immediately and show contents of container. Do not flush product down drains.

NOTES

- In new concrete surfaces, it is recommended to use the product at least after approx. 30-40 days.
- It is recommended to avoid applying the product at temperatures below 5 °C or shortly before rain.

